19

cavity to form a through hole passing between the first plane and the second plane.

- 2. The electronic device of claim 1, wherein the pattern of repeating base units extends substantially across a length and a width of the body.
- 3. The electronic device of claim 1, wherein the first spherical cavity, the second spherical cavity, the third spherical cavity, and the fourth spherical cavity are substantially a same size
- **4.** The electronic device of claim **1**, wherein the first spherical cavity, the second spherical cavity, the third spherical cavity, and the fourth spherical cavity of the pattern of repeating base units are in a three-dimensionally close-packed arrangement.
- 5. The electronic device of claim 1, wherein the first plane is parallel to the second plane.
- **6.** The electronic device of claim **1**, wherein the body conducts heat away from a component positioned substantially adjacent to the second surface.
- 7. The electronic device of claim 1, wherein the body comprises a metal.
- **8**. The electronic device of claim **1**, wherein the body comprises aluminum.
- 9. The electronic device of claim 1, further comprising a thermal spreader disposed substantially adjacent to the second surface. 25
 - 10. A housing for an electronic device, comprising: a body having a first surface and a second surface; the body defining a first set of spherical cavities extending into the body;
 - the body defining second set of spherical cavities extending into the body and eccentrically intersecting the first set of spherical cavities to form a hexagonally close-packed pattern of spherical cavities in fluid communication with a first set of apertures defined by the first surface and a second set of apertures defined by the second surface.

20

- 11. The housing of claim 10, wherein the spherical cavities of the first set of spherical cavities are substantially a same size as the spherical cavities of the second set of spherical cavities.
- 12. The housing of claim 10, wherein the first surface is substantially parallel with the second surface.
- 13. The housing of claim 10, wherein the body at least partially defines an internal volume configured to surround a component of the electronic device.
- 14. The housing of claim 10, wherein the cavities of the first set of spherical cavities are arranged in a regular and repeating pattern.
- 15. The housing of claim 10, wherein the cavities of the second set of spherical cavities are arranged in a regular and repeating pattern.
 - 16. An electronic device, comprising:
 - a body having a first surface defining a first set of apertures and a second surface opposite the first surface, the second surface defining a second set of apertures;
 - the body defining a repeating pattern of multi-planar close-packed spherical cavities in fluid communication with the first set of apertures and the second set of apertures.
- 17. The electronic device of claim 16, wherein the body is a housing that at least partially defines an internal volume.
- 18. The electronic device of claim 17, further comprising a computing component disposed in the internal volume.
- 19. The electronic device of claim 17, further comprising a fan disposed in the internal volume, the fan in fluid communication with the repeating pattern of multi-planar close-packed spherical cavities through the first set of apertures
- 20. The electronic device of claim 16, further comprising a display coupled to the body.

* * * * *